

Bathroom Art Hanging & Framing Sheet

Exact measurements and steam-ready techniques for the splash zone.

Confidently place, space, and protect your artwork against heavy humidity. This framer-approved guide delivers the exact methods you need to safely display prints.

● Clearances & Dimensions

42-45 in

floor to tub-side frame center

8 in

clearance above toilet tank lid

1/8 in

thick cork spacer dots for airflow

2

cork bumpers per frame bottom



Swap Glass for Acrylic

Traditional glass cools rapidly, trapping heavy internal condensation that ruins paper prints. Shatterproof acrylic glazing solves this thermal issue and reduces the frame's overall weight.

● Creating Airflow with Cork Dots

- 1 Clean the corners** Wipe the back bottom corners of the wooden or metal frame with rubbing alcohol.
- 2 Peel the backing** Remove the adhesive backing off the cork bumpers.
- 3 Press into place** Press one bumper firmly into the extreme lower left and right corners.

● Splash-Zone Media Guide

Find your row: **Art Medium**

Art Medium	Your pick	Why
Glazed ceramic tile	Vanity or tub ledge	Excellent humidity resistance; wipes dry
Waterproof canvas	Over the toilet tank	High resistance to heavy steam
Original watercolor	Keep out of full baths	Poor resistance to daily humidity

● Steam-Ready Framing Checklist

- ☐ Confirm shatterproof acrylic glazing is installed.
- ☐ Seal the entire backing board with waterproof foil tape.
- ☐ Attach cork spacer dots to the bottom corners.
- ☐ Specify a waterproof topcoat for bathroom canvases.
- ☐ Select the correct wall anchors for tile or drywall.

● Check Before You Hang

- Verify the toilet tank lid lifts off without hitting frames.
- Check that tub-side art aligns with a seated bather's gaze.
- Confirm your wall anchors match your specific wall material.

● Project Notes

Enjoy your beautifully styled, perfectly protected bathroom sanctuary!